

SUCCESS STORY



SILICON LABORATORIES IMPROVES VERIFICATION SPEED AND PRODUCT QUALITY USING INCISIVE ENTERPRISE SIMULATOR

Digital Mixed-Signal Option Makes Regressions
Run Dramatically Faster

HIGH PERFORMANCE, ANALOG-INTENSIVE, MIXED-SIGNAL

Founded in 1996 and headquartered in Austin, Texas, Silicon Laboratories is an industry leader in high-performance, analog-intensive, mixed-signal ICs. The company creates innovative products for the microcontroller, audio-video, modem, and subscriber line markets.

Within the Broadcast Group of Silicon Labs, which develops FM and TV tuners, a focus on analog design means that the analog design teams verify the blocks while the digital verification team integrates the digital and analog content at the chip level. Verifying the full chip with Spice (or even FastSpice) models would be prohibitively slow. As Jeff Alderson, Senior Design Engineer at Silicon Labs, commented, "Even if full chip analog simulation could have been run, it would have taken 9-10 days. Using wreal models our regressions finish in around four hours."

IT'S ALL ABOUT PERFORMANCE

Performance was a key consideration for Silicon Labs when investigating the use of Digital Mixed Signal (DMS). The DMS Option for Cadence® Incisive® Enterprise Simulator (IES) takes advantage of the wreal construct in Verilog-AMS to seamlessly connect Real Value Models (RVM) to the digital content. Because RVMs are event based, they are evaluated in the digital simulator to achieve much faster performance. "Because of the large amount of analog content in our designs, we must run full chip verifications with accurate analog models," said Jayanth Shreedhara, CAD Engineer at Silicon Labs. Silicon Labs uses RVMs to abstract the function of the analog content. "We develop the models to represent the accuracy we need. For the analog blocks that are part of a feedback loop from the digital side, those models are modeled accurately enough to simulate actual chip performance," explained Alderson.

By modeling ADCs, analog multiplexers, multipliers, sigma delta converters, filters, and other analog devices using RVM, they were able to keep the simulation of analog intensive modules in the digital domain which runs much faster than the analog solver.

QUALITY AND PRODUCTIVITY GAINS ALSO ACHIEVED

Why not just use Verilog behavioral models to represent the analog content? Connectivity checking between the analog and digital parts of the design is critical since the two domains are usually created and verified separately. The checking is often done by hand by having several layers of people manually check the connection of each pin to verify it is correct.

Verilog-D behavioral models may be written to represent the functionality, but Verilog-D is limited in its ability to pass a 64-bit real value across a port. There

"I found pin swaps and inversions that would have been difficult to find in silicon but were easy to catch and debug in simulation."

Glen Ragan, Senior Systems Engineer at Silicon Labs

SILICON LABS LOOKS FORWARD TO CONTINUED VERIFICATION PROCESS IMPROVEMENTS USING DMS OPTION

Silicon Labs has been able to take advantage of the performance, quality, and productivity improvements offered through the use of wreal and RVM. The company looks forward to using more of the advanced capabilities such as arrays of wreals and wreal resolution in their next project. Both Ragan and Alderson enthusiastically agreed that, "The new features offered with the Incisive Enterprise Simulator DMS Option will allow us to further improve our verification environment."

are also limitations with vectors of real values and resolution problems when connecting multiple real value ports. Using the Verilog-AMS wreal construct (which allows a real value to be assigned to a single-bit wire), along with the DMS Option to IES, resolves those issues.

Silicon Labs used the wreal construct along with RVMs to accurately and easily create its mixed-signal environment. And since the RVMs matched pin to pin with the Spice models, the Silicon Labs team was able to find numerous quality problems using simulation versus having to conduct multi-day design reviews where the designers go pin by pin to manually validate connectivity and polarity. As Glen Ragan, Senior Systems Engineer at Silicon Labs, stated, "I found pin swaps and inversions that would have been difficult to find in silicon but were easy to catch and debug in simulation." He also added that "having wreals react to digital inputs and vice versa was simple to construct versus having to interface to electricals. This made critical digital to analog to digital loops fairly simple to validate."

With the ease and speed of creating RVMs, the digital verification effort has been able to start sooner. "We can create RVMs very quickly and don't have to wait for the final Spice models" said Alderson. "The digital verification team has been able to take on more top-level verification responsibility because models have been quick to develop. Instead of using just simple buffers to represent the analog, the wreal models were more accurate and provided more checking. In other words, the use of wreal models in our mixed-signal verification flow, significantly improved our overall verification productivity. Overall, it reduced our regression run-time from weeks to hours with a much better quality product."

For more information
contact Cadence sales at:
+1.408.943.1234
or log on to:
[www.cadence.com/
contact_us](http://www.cadence.com/contact_us)

cadence®

Cadence Design Systems, Inc.

CORPORATE HEADQUARTERS

2655 Seely Avenue
San Jose, CA 95134
P: +1.800.746.6223 (*within US*)
+1.408.943.1234 (*outside US*)
F: +1.408.943.5001
www.cadence.com