

# Spectre AMS Designer

## Advanced mixed-signal simulation solution

The Cadence® Spectre® AMS Designer provides an advanced mixed-signal simulation solution for the design and verification of analog, RF, memory, and mixed-signal silicon realization. It is integrated with the Cadence Virtuoso® full-custom environment as well as the Cadence Xcelium™ Parallel Logic Simulator. Spectre AMS Designer provides a single-simulation executable with flexible abstraction support through the standard mixed-signal languages (Verilog-AMS and VHDL-AMS), SystemVerilog, and/or SPICE-level models. As the bridge between the analog and digital domains, it enables users to choose the right analog solver for the right design or verification task. Designers can choose Spectre technologies for SPICE-accurate block-level analog and RF designs: Spectre Accelerated Parallel Simulator (APS), Spectre RF Option, Spectre X Simulator, and Spectre eXtensive Partitioning Simulator (XPS).

### Spectre Simulation Platform

As the industry’s leading solution for accurate analog simulation, the Spectre Simulation Platform contains multiple solvers to allow a designer to move easily and seamlessly between circuit-, block-, and system-level simulation tasks. The foundation of the platform is a unified set of technologies shared by all of the engines—the parser, device models, Verilog-A behavioral modeling, input data formats, output data formats, etc.—thereby guaranteeing consistent and accurate evaluation methods regardless of the simulator selected.

Spectre Accelerated Parallel Simulator (APS) analog simulator provides Spectre accuracy with a 5X to 10X reduction in simulation time as compared to the original Spectre engine. Spectre X Simulator solves large-scale verification simulation challenges with up to 10X speed and 5X capacity improvements as well as scalable and massively parallel simulation for cloud computing. Spectre Extensive Partitioning Simulator (XPS) provides the FastSPICE high-performance and capacity simulation needed to handle memory and mixed-signal designs. The complete portfolio is rounded out by Spectre AMS Designer, Cadence’s mixed-

signal, mixed-language, mixed-level, functional, behavioral, gate-level, and transistor-level simulator.

The Spectre RF Option provides accurate and fast simulation for RFIC circuits. The option includes periodic steady-state, small-signal, and noise analyses along with harmonic balance analysis capabilities to maximize performance

without loss in accuracy. The Spectre CPU Accelerator Option enables multi-thread simulation for transient and periodic steady-state analysis, which is extremely useful for verification of parasitic back-annotated designs across multiple CPUs. The Spectre Power Option is the dedicated transistor-level electro-migration and IR drop (EM-IR) analysis




Figure 1: Spectre Simulation Platform

built into the Spectre Simulation Platform and used as the analysis engine inside the Cadence Voltus™-Fi Custom Power Integrity Solution.

Cadence provides a unique multi-mode simulation (MMSIM) license that can enable any part of the platform on demand, so you can focus on simulating your design without worrying about which licenses are required for various simulation types.

## Spectre AMS Designer

### Benefits

- Ensures design quality with proven Spectre and Xcelium simulation technologies
- Supports both analog design flow use models in Virtuoso ADE Product Suite as well as digital-verification use models in the Xcelium environment
- Supports both top-down and bottom-up methodologies to quickly detect and fix design failures early in the design cycle, helping to meet tapeout schedules
- Extensive language support allows a higher level of abstraction and accelerates simulation to achieve faster turnaround time
- Supports simulation of RF circuits at full SPICE accuracy by combining envelope analysis of RF transceivers with digital baseband simulation for faster convergence of results

### Features

#### Methodology-independent design convergence

Spectre AMS Designer provides the flexibility to combine IP from different sources and in different formats for today's SoC designs. It does more than just co-simulate analog and digital blocks. By treating Virtuoso Schematic Editor blocks and textual descriptions equally, Spectre AMS Designer allows different points of data entry. It accepts descriptions in the standard language formats of Verilog-AMS, VHDL-AMS, Verilog-A, Verilog, VHDL, SystemVerilog, and SystemC®, as well as SPICE, and performs simulation on any combination of these languages. This allows bottom-up and top-down design methodologies to converge into a fully functional design.




Figure 2: One simulator supports either verification flow

Different levels of abstraction, such as Verilog-AMS or VHDL-AMS behavioral models and schematic representation, are easily interchangeable to allow the design to change over time from full behavioral to full transistor. The entire design is configured using the hierarchy editor, which facilitates the viewing and design preparation of a complex mixed-signal design. Automatically inserted interface elements are used to translate signals from one domain to the next, leaving the user free to simulate with different design configurations to easily trade off simulation speed for simulation accuracy.

The SpectreAMS Designer also supports IP encryption using RSA technology, which allows the user to establish both IP reuse and virtual-prototyping methodologies.

#### Integrated with proven Spectre and Xcelium simulation technologies

Spectre AMS Designer is a mixed-signal simulator based on the proven technology of the Spectre Circuit Simulator, Spectre APS, Spectre X Simulator, and Spectre XPS, and the Xcelium digital simulation capabilities. You can choose different releases of Spectre and Xcelium technologies for your mixed-signal simulation.

#### Analog-centric flow with Virtuoso environment

Spectre AMS Designer is tightly integrated with the Virtuoso ADE Product Suite for mixed-signal block design. It uses native Analog Design Environment netlisting technologies to combine schematics and behavioral views, enabling users to independently manage the level of abstraction of

each block. The entire design is configured using the hierarchy editor, which facilitates the viewing and design preparation of a complex mixed-signal design.

- Using Spectre AMS Designer ensures that the user gets golden simulation results for performance measurements
- Advanced circuit analysis such as Monte Carlo analysis can be performed with the Spectre AMS Designer interface, leveraging the performance benefits of behavioral models and using the same set-up as the other Spectre simulators
- Advanced-model validation capabilities allow users to automatically verify their circuit design against a behavioral model by comparing simulation waveforms

#### Digital-centric flow with Xcelium simulation

Spectre AMS Designer works natively in the Xcelium environment for digital-centric verification. A single control file is used to define how analog blocks are integrated into the digital SoC. Analog and RTL blocks can be easily interchanged to trade off accuracy and performance. It supports all features in the Xcelium environment including testbench analysis, Cadence® technology, and verification planning.

- Automatically inserted interface elements are used to translate signals from one domain to the next, leaving the user free to simulate with different design configurations to easily trade off simulation speed for simulation accuracy.

- In the verification flow, Spectre Circuit Simulator is used as the built-in analog simulation engine, enabling verification of large mixed-signal designs. The Xcelium digital simulation engine delivers high-performance native Verilog, SystemVerilog, VHDL, SystemC, and e simulation.
- The SimVision multi-language debugging environment allows users to view analog and digital signals in a single waveform environment.
- Cross-domain connectivity between testbenches and design IP blocks from multiple vendors is enabled by providing native connectivity between VHDL or SystemVerilog and SPICE.
- Assertion-based verification for analog and digital designs is supported by extending the syntax of PSL and SVA languages, providing an efficient and effective methodology for capturing design intent and verification automation.
- Mature digital verification methodologies, such as low-power verification, are extended to the analog domain, and support capturing power intent with CPF/UPF and automatically inserting “PowerSmart” connect modules on key interfaces.

## Specifications

### Virtuoso environment

- Direct Verilog-AMS netlisting
- Hierarchy editor AMS plug-in
- Hierarchy editor configuration
- Support for global design variables and global signals
- Inherited connections

### Spectre AMS Designer

- Flexible integration of desired Spectre and Xcelium releases
- Digital and real number-modeling capabilities
- System-level simulations with links to MathWorks Simulink
- Save/restart
- Common mixed-signal waveform database

### Design inputs

- OpenAccess database
- Verilog-AMS 2.0
- VHDL-AMS 1076.1
- Verilog (IEEE 1364-1995, IEEE 1364-2001 extensions)
- VHDL (IEEE 1076-1987, IEEE 1076-1993, IEEE 1076.4-2000 [VITAL 2000])
- Spectre and SPICE netlist formats
- SystemVerilog (IEEE 1800)
- Unified Power Format (UPF) or Common Power Format (CPF)

### Xcelium platform

- SystemC (OSCI SystemC v2.01) and SystemC Verification Library (OSCI SCV 1.0)
- Specman technology

## Specifications

### Comprehensive list of analog device models supported

- Advanced-node models, including the latest versions of the BSIM CMG, BSIM IMG, and UTSOI models
- MOSFET models, including the latest versions of the BSIM3, BSIM4, BSIM Bulk (BSIM6), PSP, and HiSIM
- High-voltage MOS models, including the latest versions of the HiSIM HV, MOS9, MOS11, and EKV
- Silicon-on-insulator (SOI), including latest versions of BTASOI, SSIMSOI, BSIMSOI, BSIMSOI PD, and HiSIM SOI
- Bipolar junction transistor (BJT) models, including the latest versions of VBIC, HICUM, Mextram, HBT, and Gummel-Poon models
- Diode models, including the diode, Phillips level 500, and CMC diode models
- JFET models, including the JFET, Phillips level 100 JFET, and Individual dual-gate JFET models
- IGBT models, including PSpice® IGBT model and HiSIM IGBT models

- Resistors, including linear resistor, diffused resistor, CMC two-terminal and three-terminal resistor, and physical resistor models
- GaAs MESFET models, includes latest versions of GaAs, TOM2, TOM3, and Angelov
- GaN MESFET models, including Angelov, ASM, and MVSG models
- Silicon TFT models, including RPI Poly-Silicon and Amorphous Silicon Thin-Film models
- Verilog-A compact device models
- Z and S domain sources
- User-defined compiled model interface (CMI), allowing for the rapid inclusion of user-defined models
- Josephson Junctions
- Specialized reliability models (AgeMOS) for simulating the effect of HCI and BTI
- Miscellaneous power models, including the relay, transformer, non-linear magnetic core, and winding
- Miscellaneous RF models, including the dc block, dc feedthrough, and microstrip and stripline elements (bend, cross, corner, curve, open line, tee models)

### Language and netlist support

The netlist formats, behavioral modeling languages, parasitic netlist formats, and stimulus files are common across the Spectre Simulation Platform. Supported formats include:

- Spectre and SPICE netlist formats
- Spectre, SPICE, and PSpice models
- Verilog-A 2.0 LRM-compliant behavioral models and structural netlists
- DSPF/SPEF parasitic formats
- S-parameter data files in Touchstone, CITI-file, and Spectre formats
- SST2, PSF, PSF XL, and FSDB waveform formats
- Digital vector (VEC), Verilog-Value Change Dump (VCD), Extended Verilog-Value Change Dump (EVCD), and digital stimulus

## Platform support

- x86 64-bit Red Hat Enterprise 6.5 (and higher) and V7, SLES 11 and 12
- Commercially available cloud solutions

## Cadence Services and Support

- Cadence application engineers can answer your technical questions by telephone, email, or Internet—they can also provide technical assistance and custom training.
- Cadence-certified instructors teach more than 70 courses and bring their real-world experience into the classroom.
- More than 30 Internet Learning Series (iLS) online courses allow you the flexibility of training at your own computer via the internet.
- Cadence Online Support gives you 24x7 online access to a knowledgebase of the latest solutions, technical documentation, Rapid Adoption Kits, software downloads, and more.
- For more information, please visit [www.cadence.com/support](http://www.cadence.com/support) for support and [www.cadence.com/training](http://www.cadence.com/training) for training.



Cadence software, hardware, and semiconductor IP enable electronic systems and semiconductor companies to create the innovative end products that are transforming the way people live, work, and play. The company's Intelligent System Design strategy helps customers develop differentiated products—from chips to boards to intelligent systems. [www.cadence.com](http://www.cadence.com)

© 2019 Cadence Design Systems, Inc. All rights reserved worldwide. Cadence, the Cadence logo, and the other Cadence marks found at [www.cadence.com/go/trademarks](http://www.cadence.com/go/trademarks) are trademarks or registered trademarks of Cadence Design Systems, Inc. SystemC is a trademark of Accellera Systems Initiative Inc. All other trademarks are the property of their respective owners. 12991 08/19 SA/RA/PDF